


# SPECIFICATIONS

## Features



- Constant Current Output
- 0-10V Dimming
- Class II Compliance
- Damp Location
- 5 Year Warranty
- Hot Wire Protection
- Supporting DIM TO OFF Capability
- Bottom / Side wire insert

## Wiring Diagram



## Mechanical and Thermal

Dimensions L3.878" x W2.047" x H1.171"  
 Weight 285 g  
 Lead Wire Length Push in connector  
 Max. Case Operation Temp. 80°C



## Protection


- Auto-reset electronic short circuit
- Overload protection
- Inherent Thermal Protection
- Hot Wire Protection

## Environmental Specifications

- Operating Temperature -20° to 60°C
- Storage Temperature -20° to 70°C
- MTBF >100,000 hrs
- Lead Free SMT process
- RoHS compliant

## Electrical

Maximum Load 23W  
 Input Voltage 120 – 277V/50-60Hz  
 Output Voltage 22-33VDC  
 Output Current (max.) 700mA  
 Power Factor >0.90 (15-23W)  
 Efficiency @ 80% Load Min 80 typ.  
 No Load Loss <1 W



(Bottom stud is illustrated, Bottom stud is optional)

Note –

1. UL file No.: E340871
2. Driver is designated for “Stand by mode” at minimum light intensity (<0.8Vdc) power will not be OFF.



Macron Associate Co. – Power Supply Team

NO.352, Peng-Yi Road, Taiping, Taichung, Taiwan 411

TEL: 886-4-22708357 FAX: 886-4-22767307 Email: macron@macrongroup.com

B1214