


SPECIFICATIONS

Features

- Constant Current Output
- 0-10V Dimming
- Class 2 Compliance
- Damp Location
- 5 Year Warranty
- Hot Wire Protection
- Supporting DIM TO OFF Capability
- Intelligent Control/Support MOC1 Occupancy Sensor module
- Constant Current Reduction (CCR)

Mechanical and Thermal

Dimensions	L7.874" X W1.102" X H0.866"
Weight	140g
Lead Wire Length	Terminal blocks
Max. Case Operation Temp.	80°C




* Dimension in Inch

Electrical

Maximum Load	15W
Input Voltage	120 – 277V/50&60Hz
Output Voltage	28-43VDC
Output Current (max.)	350mA
Power Factor	>0.90 (11-15W)
Efficiency @ 80% Load Min	80 typ.
No Load Loss	<1 W

Wiring Diagram



Protection

- Auto-reset electronic short circuit
- Overload protection
- Class 2
- Inherent Thermal Protection

Environmental Specifications

- Operating Temperature -20° to 60°C
- Storage Temperature -20° to 70°C
- MTBF >100,000 hrs
- Lead Free SMT process



Note –

1. UL file No.: E340871
2. Driver is designated for “Stand by mode” at minimum light intensity (<0.8Vdc) power will not be OFF.



Macron Associate Co. – Power Supply Team

NO.352, Peng-Yi Road, Taiping, Taichung, Taiwan 411

TEL: 886-4-22708357 FAX: 886-4-22767307 Email: macron@macrongroup.com

C0618