


SPECIFICATIONS

Features


- Work for most 3-wire/2-wire dimmer
- Compact size/ Low profile
- Constant Current Output
- Active Power Factor
- Class 2 compliance
- 5 Year Warranty
- Restart at Lowest Dimming Setting

Wiring Diagram



Mechanical and Thermal

Dimension L 5.709" × W 1.811" × H 1.260"
 Lead Wire Length Push In Connector
 Max. Case Operation Temp. 80°C



* Dimension in Inch/Metric

Protection

- Auto-reset electronic short circuit
- Overload protection
- Thermal protection
- Class 2

Environmental Specifications

- MTBF >100,000 hrs
- RoHS Compliant
- Lead Free SMT process
- Power Factor Correction / Low Load

Electrical

Maximum Load	23W
Minimum Load	18W
Input Voltage	120-277V
Max Output Voltage/Current	38VDC/600mA
Power Factor	>0.90
Max. Harmonic Distortion	<20%
Efficiency	85 typ.
No Load Loss	<1 W



Note –

1. UL file No.: E340871



Macron Associate Co. – Power Supply Team

NO.352, Peng-Yi Road, Taiping, Taichung, Taiwan 411

TEL: 886-4-22708357 FAX: 886-4-22767307 Email: macron@macrongroup.com

A0218