



Macron Associate co.  
www.macrongroup.com  
Email:macron@macrongroup.com  
Tel:+886 4 22708357 Fax:+886 4 22774516  
Address:No.352, Peng-Yi Road, Taiping, Taichung, 41146, TAIWAN R.O.C

---

## Macron

---

Client:

LumCAT: SPECTER S3-W-3000K 90CRI

Luminaire:

Report No:

Voltage(V):

Test No:

Current(A):

LampCAT:

Power (W): 19.7860

Lamp flux(lm): 1202.0

PF:

Number of Lamps: 1

Ballast type:

Length(mm): 0

Width(mm): 0

Phm Type: C

Height(mm): 0

---

## Photometric Results

---

Lumens(lm): 1202.64

Efficiency(%): 100.00%

Lumens(lm)/Power(W): 60.78

Central intensity(cd): 2888.955

Maximum intensity(cd): 2888.955

Angle of maximum intensity: C=0.0  $\gamma$ =0.0

Beam Angle(50%Imax): [C0/180]Total=36.0

[C90/270]Total=36.0

Field angle(10%Imax): [C0/180]Total=62.0

[C90/270]Total=62.0

Maximum s/h(1/2): C0\_180=0.60 C90\_270=0.60

Maximum s/h(1/4): C0\_180=0.59 C90\_270=0.59

Up flux rate of lamp(%): 0.00%


Down flux rate of lamp(%): 100.05%


Up flux rate of LUM(%): - -

Down flux rate of LUM(%): 100.00%

CIE Type : Direct lighting

Output flux ratio in  $\pi$  solid angle : 98.446%





Max , Ave      Beam angle of C0 plane 36.15