
Pendant Cylinder, Wallwash, length 100mm

RFV 3





Description

VAL SS features remote drivers with 3-in-1 dimming technology, twist-lock installation mechanism, best-in-class light quality, aesthetic proportions and many more. VAL is designed to integrate with architectural space with clean and distinct outline that complement architectural aspiration.

Features

 LED
 Lumiled Luxeon COB1203

 Color temperature
 2700K/ 3000K/ 3500K/ 4000K

Optics Wallwash

Electrical and Control

Input voltage36vdcControlRemote driverFeature350 mA MAX

Construction

Material Casting & Extrusion grade Aluminum Alloy

Finishes Black body with black trim/

White body with black trim

Optics Field Interchangeable optics

Performance

Delivered output Up to 735 lm(90+ CRI)

Power consumption 10 V

Color rendering 90+ CRI (80 CRI+ optional)

CBCP

Lumen maintenance L80 B10 50,000 Hours

Rating/ Certification/ Warranty

- · Dry and damp Locations
- · RoHS compliant
- · 5 years/ 50,000 hrs warranty

Ordering Code Information

PRODUCT	MOUNTING TYPE	SHAPE	LENGTH	COLOR TEMPERATURE	FINISH	BEAM ANGLE	COLOR RENDERING
VAL 55 CP WW	SS	R	10	27	WHBK	W	9
VAL 55 CY WW, Cylinder Surface Mount	Surface spot	R (Round)	10 (100 mm)	27 (2700K) 30 (3000K) 35 (3500K) 40 (4000K)	WHBK (White/Black) BKBK (Black/Black)	W (Wide)	9 (90 CRI+)



Recommend LED Driver:

Note

Driver No.	Input Voltage	<u>Dimming</u>
DE-1-250-10	120V	TRIAC/ELV
DA-1-250-10	120-277V	0-10V

Photometrics

10W | 90CRI | 3000K | White body with Black trim


MULTIPLYING FACTORS: (Multiplying Factor is based on 3000K-90+CRI IES file on website)

CCT	2700K-80+	3000K-80+	3500K-80+	4000K-80+
Factors	1.12	1.15	1.17	1.22
COT	27001/ 00 :	20001/ 001	25001/ 00:	40001/ 00 :

CCT 2700K-90+ 3000K-90+ 3500K-90+ 4000K-90+ Factors 0.97 1.0 1.04 1.04

Wall Wash

Delivered Ourput: 735 lm



Center Beam Intensity	Beam Width	Height
507 lx	142cm	1m
127 lx	283cm	2m
56 lx	425cm	3m
32 lx	567cm	4m
20 lx	708cm	5m

Optional Accessory

Product Canopy size FINISH

VAL 55 CY WW 5-2 PL WH

VAL 55 CY WW, 5-2 PL WH White BK Black

